



ZEBRONICS

ZEB-IPPBSL5

Surveillance Bullet camera

5 MP

4 IR
ARRAY
LED

20 METER
IR RANGE

AWB / HLC /
BLC / AGC

DNR /
DWDR /
ICR

NIGHT
VISION
WITH
COLOR

Features

- ICR / AGC / BLC / AWB / HLC • WDR / DNR / DWDR • 4 IR Array LED • 5 Mega Pixels
- 20M IR Range (Max.) • Weather Proof • Low Illumination

Specifications

Camera	Image Processor	1/2.7" cmos sensor
	Minimum Illumination	0.03 Lux@F2.0 (Color, 30 IRE) 0.003 Lux@F2.0 (B/W, 30 IRE) 0 Lux (IR on)
	Image Sensor	1/2.9" cmos sensor
	Shutter Speed	1/50(1/60) to 1/100,000 seconds
	Angle of View	3.6mm: Horizontal: 92°; Vertical: 48°; Diagonal: 109°
	Scanning System	Progressive Scan
Lens	Focus Length	3.6 mm (Fixed)
	Mount Type / Lens	M12
	Focus Control	Fixed
	Lens Type	Removable
	Auto Iris	Support
	Lens	3.6mm
	Max Aperture	F2.0
Night Vision	IR Cut Filter	Yes
	IR Range	20 Meters
	IR Power On	Auto Control
Camera Features	OSD Support	No
	No of IR LEDs	4 array IR LED
	Day/Night	Support
	Picture Adjustment	Yes
	WDR	Yes
	White Balance	Automatic
	AGC (Gain Control)	Yes
	ICR (Infrared Cut Removable Filter)	Auto(ICR) / Color / B/W
	Back Light Compensation	BLC / HLC / WDR
	Video output	Main stream: 2880 × 1620 (1 fps–20 fps) 2688 × 1520 (1 fps–25/30 fps) Sub stream: 704 × 576 (1 fps–25 fps) 704 × 480 (1 fps–30 fps)



ZEBRONICS

ZEB-IPPBSL5

Surveillance Bullet camera

5 MP

**4 IR
ARRAY
LED**

**20 METER
IR RANGE**

**AWB / HLC /
BLC / AGC**

**DNR /
DWDR /
ICR**

**NIGHT
VISION
WITH
COLOR**

Camera Features	Video Compression	H.265
	Weatherproof Standard	IP66 Weather-Proof
	S/N Ratio	>120dB
	Reset	Yes
General	Power Consumption	DC12V±10%, 500mA to 1A / 7.5W to 10W POE
	Operating Temperature	10°C ~ +60°C/ Less than 95%RH
	Weight	200g
	Body type	Metal Body
	Dimension (Dia x H)	7.5 x 17.88 x 6.9 in cm
	Country of Origin	India