

ZEB-AHDPDSL24

Surveillance Dome camera



5 MPL

2 IR
ARRAY
LED

20 METER
IR RANGE

DWDR /
ICR

NIGHT
VISION
WITH
COLOR

DNR /
AWB / HLC /
BLC / AGC

Features

ICR / AGC / BLC / AWB / HLC • WDR / DNR / DWDR • AHD / CVI / TVI / CVBS
• 2 IR Array LED • 5 MPL • 20M IR Range (Max.) • CMOS Image Sensor • Low Illumination

Specifications

Camera	Image Processor	1/2.9" 2.4MP hd cmos sensor
	Minimum Illumination	Color : 0.01 lux@F2.0, AGC ON B/W : 0 lux with IR
	Image Sensor	1/2.9" cmos sensor
	Shutter Speed	1/50(1/60) to 1/100,000 seconds
	Angle of View	3.6 mm: 100° x 84° x 45° (diagonal x horizontal x vertical)
	Scanning System	Progressive Scan
Lens	Focus Length	3.6 mm (Fixed)
	Mount Type / Lens	M12
	Focus Control	Fixed
	Lens Type	Removable
	Auto Iris	Support
	Lens	3.6mm
	Max Aperture	F2.0
Night Vision	IR Cut Filter	Yes
	IR Range	20M
	IR Power On	Auto control
Camera Features	OSD Support	No
	No of IR LEDs	2 Array IR LED
	Day/Night	Support
	Noise Reduction	3D NR
	Picture Adjustment	Yes
	WDR	Yes
	White Balance	Automatic
	AGC (Gain Control)	Auto / Manual
	ICR (Infrared Cut Removable Filter)	Auto(ICR) / Color / B/W
	Back Light Compensation	BLC / HLC / WDR
	Video output	CVI: 2.4MP (1920x1080p) @25/30fps; 720p@25/30fps; AHD: 2.4MP (1920x1080p) @25/30fps; 720p@25/30fps; TVI: 2.4MP (1920x1080p) @25/30fps; 720p@25/30fps; CVBS: 960H(PAL/NTSC)



ZEBRONICS

ZEB-AHDPDSL24

Surveillance Dome camera

5 MPL

2 IR
ARRAY
LED

20 METER
IR RANGE

DWDR /
ICR

NIGHT
VISION
WITH
COLOR

DNR /
AWB / HLC /
BLC / AGC

Camera Features	Video Compression	H.265
	Weatherproof Standard	No
	S/N Ratio	>50dB
	Reset	Yes
General	Power Consumption	DC12V±10%, 500mA
	Weight	140 g
	Operating Temperature	10°C ~ +60°C/ Less than 95%RH
	Body type	ABS Plastic
	Dimension (Dia x H)	9 x 7 in cm
	Country of Origin	India