

ZEB-IPDLS5

Surveillance Dome camera



5 MP

2 IR
ARRAY
LED

20 METER
IR RANGE

AWB / HLC /
BLC / AGC

NIGHT
VISION
WITH
COLOR

DNR /
DWDR /
ICR

Features

- ICR / AGC / BLC / AWB / HLC • WDR / DNR / DWDR • 2 IR Array LED • 5 Mega Pixels • 20M IR Range (Max.)
- CMOS Image Sensor • Low Illumination • Night Vision with Color

Specifications

Camera	Image Processor	1/2.7" cmos sensor
	Minimum Illumination	0.03 Lux@F2.0 (Color, 30 IRE) 0.003 Lux@F2.0 (B/W, 30 IRE) 0 Lux (IR on)
	Image Sensor	1/2.9" cmos sensor
	Shutter Speed	1/50(1/60) to 1/100,000 seconds
	Angle of View	3.6mm: Horizontal: 92°; Vertical: 48°; Diagonal: 109°
	Scanning System	Progressive Scan
Lens	Focus Length	3.6 mm (Fixed)
	Mount Type / Lens	M12
	Focus Control	Fixed
	Lens Type	Removable
	Auto Iris	Support
	Lens	3.6mm
	Max Aperture	F2.0
Night Vision	IR Cut Filter	Yes
	IR Range	20 Meter
	IR Power On	Auto Control
Camera Features	OSD Support	Yes
	No of IR LEDs	2 array IR LED
	Day/Night	Support
	Picture Adjustment	Yes
	WDR	Yes
	White Balance	Automatic
	AGC (Gain Control)	Auto / Manual
	ICR (Infrared Cut Removable Filter)	Auto(ICR) / Color / B/W
	Back Light Compensation	BLC / HLC / WDR
	Video output	Main stream: 2880 × 1620 (1 fps–20 fps) 2688 × 1520 (1 fps–25/30 fps) Sub stream: 704 × 576 (1 fps–25 fps) 704 × 480 (1 fps–30 fps)

ZEB-AHDPBSL24

Surveillance Dome camera



5 MP

**2 IR
ARRAY
LED**

**20 METER
IR RANGE**

**AWB / HLC /
BLC / AGC**

**NIGHT
VISION
WITH
COLOR**

**DNR /
DWDR /
ICR**

Camera Features	Video Compression	H.265
	Weatherproof Standard	NO
	S/N Ratio	>120dB
	Reset	Yes
General	Power Consumption	DC12V±10%, 500mA to 1A / 7.5W to 10W POE
	Operating Temperature	10°C ~ +60°C/ Less than 95%RH
	Weight	210 g
	Body type	ABS Plastic
	Dimension (Dia x H)	10.5 x 8.7 in cm
	Country of Origin	India