

ZEB 4PG2UG1UF 65

4 Port POE Switch



SFP Port

**65W
Output (Max.)**

AI Watchdog

**4 Self Adaptive
PoE Ports**

**Dual Gigabit
Uplink Ports**

Features

- 4 Self Adaptive PoE Ports • Dual Gigabit Uplink Ports • SFP Port • 65W Output (Max.)
- Upto 30W Per Port • AI Watchdog Function • High Data Rate • Wide Compatibility • Short Circuit Protection
- Anti Interference Capability • Lightning & Surge Protection • Dynamic Power Control

Specifications

Connector Type	4 Ports 1000M PoE + 2 Ports 1000M Ethernet Uplink + 1 1000M SFP Port
Network Protocols	IEEE802.3/802.3u, IEEE802.3x, IEEE802.3ab
PoE Parameters	PoE Standard: IEEE802.3af (15.4W) & IEEE802.3at (30W)
	PoE Compatibility: IEEE802.3af/at Self Adaptive
	Power Pin Assignment : MODE A [1/2(+), 3/6(-)]
Network Media	10BASE-T: <250 meters
	100BASE-TX: <100 meters
	1000BASE-T: <100 meters
Power Supply	Input: AC100-240V, 50/60Hz
	Output: 30W Per Port
	Power Budget: 65W
Performance Specification	Bandwidth: 14Gbps
	MAC: 2K
	Packet Buffer Memory: 2Mbits
	10M Packet Forwarding Rate: 14880pps/port
	100M Packet Forwarding Rate: 148800pps/port
LED Indicator	1000M Packet Forwarding Rate: 1488000pps/port
	Power (Red): Lit - Powered, Unlit - No Power
Working Environment	Ethernet (Green) : Flash - Data Transmit, Unlit - Disconnect
	Operating Temperature: -10°C ~ 55°C
	Storage Temperature: -20°C ~ 70°C
	Operating Humidity: Max 20 ~ 95% (Non-condensation)
Physical Parameter	Storage Humidity: Max 20 ~ 95% (Non-condensation)
	Product Dimension (W x D x H) : 19 x 12.5 x 3.8cm
	Package Dimension (W x D x H) : 20 x 19.6 x 4.8 cm
Transmission Distance	Net. Weight: 579g
	Data Transmission Distance: 250m (Max.)
Port Surge Protection	PoE distance upto 250 meters with 10M via Cat.6
Forwarding Mode	6KV
	Store and forward