



ZEBRONICS

ZEB-MLS755


Uninterruptible Power Supply



**OVERLOAD
PROTECTION**



**SLEEP MODE
CHARGING**



**GENERATOR
COMPATIBLE**



**SUPPORTS
MICRO LOAD**

Features

- Line interactive UPS • Auto restart while AC is recovering • Backup of upto 3h 45min* for micro power consumption devices
- Double Boost • Automatic Voltage Regulation (AVR) • Wide Input Range • Cold Start • Boost & Buck AVR • LED & Audible Alarms

Specifications

Capacity	(VA/W)	600VA/360W
Input	Nominal Voltage	AC 220-240 V
	Voltage Range	AC 140-300 V
	Frequency	50/60 Hz
	Plug Type	3 Pin Plug
	Input Protection	Internal Fuse
Output	Voltage Range (AC mode)	230VAC \pm 10 %
	Voltage Range (Batt. Mode)	230VAC \pm 10 %
	Frequency Range (Batt. Mode)	50/60Hz \pm 1%
	Transfer Time	4-8ms
	Waveform	Simulated Sine Wave
	No. of Output Sockets	3
	Protections	Overload, Short Circuit, Over Discharge & Over Charge
Record Mode	Battery Type	12V 7Ah x 1 nos
	Charging Current	1A
	Recharge Time	6-8h to charge 90% (after complete discharge)
Indicators	No. Of LEDs	3 LED
	AC Mode	Green LED Glows
	Battery Mode	Orange LED blinks
	Fault Mode	Red LED Glow
Alarm	Battery Mode	Beeping every 10 Seconds
	Low Battery	Beeping every 1 Second
	Overload	Beeping every 0.5 second
	Fault	Continuous Beeping
Physical Details	Dimension (W x D x H)	10.5 x 27.6 x 14.4 cm
	Net Weight	3.9 kg
	Package Dimension (W x D x H)	32.6 x 14.2 x 21.3 cm
Environmental Factors	Operational Temperature	0-40°C
	Noise Level	< 45dB